

Aplex

The Aplex 30/100 Zone Multiplex Security Controller offers the ideal flexible and powerful solution to Commercial, Industrial and High Security applications. A library of programs is available for applications such as Banking, Schools, Retail Stores, Guard Tour, Multi-Block Systems and others.

• Features

- Aplex 30: 30 zones, 15 remote outputs
- Aplex 100: 100 zones, 50 remote outputs
- Cable: 4 or 6 core unscreened alarm cable 2km
- Display: 20 character LED on control panel and RKDs
- Log: 500 events, with date and time
- Users: 34 General, 1 Master, 1 Engineer
- Serial I/O: For printer/PC/synoptique system
- Set up: Locally/Remotely via modem/PC
- Zone Types: 26
- Analogue multiplexing, with all zones EOL resistor monitored loops (Dual 2 x 2k2)
- Complete wiring flexibility with all input/output modules allowing complete flexibility in numerical sequencing
- All system functions available from panel keypad or RKDs
- Zone descriptions/user names displayed in clear text
- Engineer settable automatic time commands
- ACPO option available

• Compatible Equipment

- Line Encoder Modules: A LEM: 2 Zones
- Surface mount A LEM (SMT): 2 Zones
- Quad LEM: 4 Zones
- C LEM 1 Output (2A relay)
- Multi I/O Modules
- Remote Keypad: Polycarbonate
- DM1200: Digital communicator/modem



• Software Options

- 3 Area/8 Area
- Eurobank (High Security Application)
- Panelman (PC set up)
- Euronetwork/Eurodial/Maps

• Networking

- "Euronetwork" software monitoring
- 12 Aplex panels up to 2km apart
- Real time display on PC of each Aplex
- Remote control of each system
- Colour graphics option with Master map and up to 26 sub-maps per Aplex

• Remote Servicing

- "Eurodial" software, allowing access to remote Aplex sites via modem and PC
- Colour graphics option, as above

For more details

For more information on this product, please see the Aplex Installation Guide.



