



Proven. Secure.

FLEXPASS

ARCH

A BOLD STATEMENT. THE ARCH COVER DESIGN PRODUCES A UNIQUE LOOK BY COMBINING SYMMETRICAL GRIDS AND COMPLEMENTARY ARCHES.



ARCH



AVAILABLE IN: BLACK GREY WHITE BEIGE

INDALA PROVIDES A COMPLETE PRODUCT PORTFOLIO WITH THE FLEXSECUR™ TECHNOLOGY - THE CONFIDENCE OF SECURITY BETWEEN CARD AND READER. SUPPORTED WITH INNOVATIVE DESIGN AND RESPONSIVE CUSTOMER CARE.

FLEXPASS™

An ASSA ABLOY Group company

ASSA ABLOY

SPECIFICATIONS

Size Slim: 4.5" H x 1.7" W x 0.8" T (11.4cm x 4.3cm x 2.0cm)
 Wallswitch: 4.5" H x 3.0" W x 0.8" T (11.4cm x 7.6cm x 2.0cm)
 Mid-Range: 5.1" H x 6.1" W x 1.1" T (13.0cm x 15.5cm x 2.8cm)

Read Range Slim: Up to 5" (12.7cm) using FlexCard™ standard card
 Wallswitch: Up to 5" (12.7cm) using FlexCard standard card
 Mid-Range: Up to 12" (30.5cm) using FlexCard standard card

Input Voltage Slim: 4-16 VDC at reader Wallswitch: 4-16 VDC at reader
 Mid-Range: 4-14 VDC at reader

Typical Current Draw

Off Metal: Slim: 65 mA @ 12 V; 86 mA @ 5 VDC
 Wallswitch: 65 mA @ 12 V; 86 mA @ 5 VDC
 Mid-Range: 117 mA @ 12 V; 70 mA @ 5 VDC

On Metal: Slim: 86 mA @ 12 V; 97 mA @ 5 VDC
 Wallswitch: 86 mA @ 12 V; 97 mA @ 5 VDC
 Mid-Range: 111 mA @ 12 V; 65 mA @ 5 VDC

Maximum: Slim: 96 mA @ 12 V; 100 mA @ 5 VDC
 Wallswitch: 96 mA @ 12 V; 100 mA @ 5 VDC
 Mid-Range: 140 mA @ 12 V; 82 mA @ 5 VDC

Operating Temperature -31° to +149°F (-35° to +65°C)

LED Indicator Tri-color standard (red, green, amber)

Audio Tone Standard, independently controllable (not tied to LED)

Output Formats Wiegand, ABA Track II Magnetic Stripe, and Serial TTL (requires use of BIL 232/422 Module)

Frequency 125 kHz (excitation)

Read Time (26-bit) 200 ms (from read to data output)

Security Various levels (configurable) FlexSecur™

Programming Factory or field programmable via FlexPass ProxSmith Programmer and Toolkit

Colors Black, Grey, White, Beige

Other Features Self Test, QuickFlash, WatchDog

Product Description	Package* Part #	Bezel Only Part #	CEM Only Part #
Slim, Black	FP3511A	FPZ-3511A	FPC-0500A
Slim, Grey	FP3515A	FPZ-3515A	FPC-0500A
Slim, White	FP3516A	FPZ-3516A	FPC-0500A
Slim, Beige	FP3517A	FPZ-3517A	FPC-0500A
Wallswitch, Black	FP3521A	FPZ-3521A	FPC-0500A
Wallswitch, Grey	FP3525A	FPZ-3525A	FPC-0500A
Wallswitch, White	FP3526A	FPZ-3526A	FPC-0500A
Wallswitch, Beige	FP3527A	FPZ-3527A	FPC-0500A
Mid-range, Black	FP3231A	FPZ-3231A	FPC-0200A
Mid-range, Grey	FP3235A	FPZ-3235A	FPC-0200A
Mid-range, White	FP3236A	FPZ-3236A	FPC-0200A
Mid-range, Beige	FP3237A	FPZ-3237A	FPC-0200A
Mid-range, Black, Serial	FP3231S	FPZ-3231A	FPC-0200S
Mid-range, Grey, Serial	FP3235S	FPZ-3235A	FPC-0200S
Mid-range, White, Serial	FP3236S	FPZ-3236A	FPC-0200S
Mid-range, Beige, Serial	FP3237S	FPZ-3237A	FPC-0200S

*Packages include Core Electronics Module (CEM) and Bezel.



SLIM



WALLSWITCH



MID-RANGE

Credentials

The Indala FlexPass Arch is designed to work seamlessly with Indala FlexPass credentials such as the FlexISO™, FlexKey™ and FlexCard.

APPROVALS

UL 294/cUL, FCC Certification - United States, Canada Certification, CE Mark - Europe, Australia C-Tick, New Zealand/EMC

WARRANTY

Indala warrants this product against defects in material and workmanship under normal use and service. The warranty period commences with the date of shipment. See complete warranty statement for further details.

Read range stated when readers installed according to instructions. Read range may vary when mounted on metal and with different cover designs. Illumination colors may differ based on cover design color. Specifications subject to change without notice. Indala reserves the right to discontinue any product without notice.

Indala, FlexPass, and all other trademarks indicated as such herein are registered trademarks of Indala, an ASSA ABLOY Group company. © U.S. Pat. & Tm. Off. All other products or service names are the property of their respective trademark owners.

© 2002 Indala. All rights reserved. Printed in the U.S.A.
 archds 10-2002



6850 B Santa Teresa Blvd.
 San Jose, California 95119-1205 USA
 Toll Free: 800-779-8663 (USA only)
 Tech Support: 800-646-3252 (USA only)
 Phone: +1 408-361-4700
 Fax: +1 408-361-4701

European Office
 Unit 1, The Deans
 Bridge Road
 Bagshot, Surrey
 GU19 5AT
 United Kingdom
 Phone: +44 (0) 1276-477-400
 Fax: +44 (0) 1276-477-430

Asia Pacific
 Identification Technology Group
 Asia Pacific, Ltd.
 19/F 625 King's Road
 North Point
 Island East
 Hong Kong
 Phone: +852 2530 9907
 Fax: +852 2530 9975

www.indala.com